

PRESSURE SENSITIVE TEXTURED VINYL



One product, endless applications. Create floor, wall and window graphics with one universal media ... Trifecta[®].

Trifecta

6 mil semi-rigid matte white textured facestock rated for <5 years of outdoor use High opacity film with an excellent white point

Universal removable adhesive that will cleanly remove from indoor and outdoor applications for <6 months

Stable 90# layflat polycoated paper liner for ease of printing and installation

Print Compatibility: Wide Format (Solvent, Eco-Solvent, Latex and UV), UV Offset and Screen

When to use Trifecta

One-Step Floor Graphics - Create UL 410 slip resistant floor graphics in one easy step... no overlaminate required. Easy to install and remove. Trifecta® is suitable for indoor short term floor graphics (<6 months). *Not intended for outdoor floor graphic applications. For best results, we recommend printing floor graphics with UV inks to avoid potential scuffing.. *Not intended for outdoor floor graphic applications.

Wall Graphics - Hassle free textured wall decals - peel, stick, done. No need for tapes, tacks or nails and will remove cleanly from painted dry wall.

Window Graphics - Enhance the look of standard window graphics with a dimensional, textured finish. Perfect for short term decorative window decals smaller than 2' x 2'.

Applications

One-Step Floor Graphics

Wall Graphics

Window Signage

Social Distancing Floor Graphics

Counter Mats

Posters

Wall Décor

Wayward Signage

Directional Arrows

One-Way Window Graphics

Floor Advertisement

Point-of-Purchase Signage

















STOCKED PRODUCTS ▶

	Finish/Color	SKU#	Size	Thickness	Adhesive	Liner	Rolls/Carton
Wide Format							
	Textured Matte White	SPMTRI54100	54" x 100 ft	6 mil	Universal Removable	90# Layflat	1

Easy to apply and remove from these surfaces:













CUSTOM SIZE OFFERING ▶

	Finish/Color	SKU#	Size (width)	Film Thickness	Adhesive	Liner	Wgt/MSI
Non Top Coat	ed - UV Offset, Screen						
	Textured Matte White	TRIFECTA	54"	6 mil	Universal Removable	90# Layflat	.64#

Custom Size Offering: Custom converted sheet and roll options available to meet your specific requirements.









TECHNICAL DATA ▶

		Trifecta	
Physical Properties			
Finish		Textured	
Color	Color		
Adhesive	Adhesive		
Film	Film Liner Opacity		
Liner			
Opacity			
Gloss Level	Gloss Level		
	Film	6 ± 0.2 mil	
Thickness	Film w/ Adhesive	6.7± 0.2 mil	
	Total Thickness	13.2±0.4 mil	
Adhesion	SS 15 min Room Temp Dwell	16-20 oz/in	
Adilesion	SS 24 hr Room Temp Dwell	23-27 oz/in	
Weight	Film w/ Adhesive	265-270 gsm	
Weight	Total w/ Liner	410-420 gsm	
Slip Resistant Certific	Slip Resistant Certification		

Conditions for Use	
Shelf Life	1 year
Clean Removability	Up to 6 months
Outdoor Durability	Up to 5 years
Min Application Temp	40° F (4° C)
Service Temp Range	-20° to 150° F (-29° to 66° C)
Solvent Resistance	Good*
Water Resistance	Excellent

CPSIA Compliant

*Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended.

The information provided herein is correct to the best of Nekoosa's knowledge, however, should not be construed as specifications. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

